



# PortaDAP BASIC



The **BASIC**, one of the world's bestselling audioguides, offers a « unique » solution that answers all of a site's worries with traditional audioguides: with merely two disposable AA alkaline batteries, the **BASIC** can continuously play approximately 350 hours of messages, which means around three and a half months of autonomy in general usage without recharging! Therefore, no charging racks are needed. By dispensing with use of charging racks, the **BASIC** dramatically decreases handling, management, and storage needs. The **BASIC** sells at a very affordable price and provides unparalleled reliability levels: **less than 3% returns per year!**  
**Your « answer »? ...**

## Your « answer »...

### Extremely reliable

Designed for absolute reliability: defect rates do not exceed 3% per year, even for the most busy sites.

### Minimum handling and storage needs

Using two disposable AA alkaline batteries, the **BASIC** has around three and a half months of autonomy in general usage, without recharging! Therefore, no charging racks are needed.

By dispensing with using charging racks, the **BASIC** dramatically decreases handling and storage needs.

### Minimum operational costs

Extreme reliability, minimum handling (no daily recharging), and easy management (easy message programming, language change, and statistics retrieval) mean smoother operations, reduced personnel numbers, and lesser running costs!

### Simple to program

The programming of visits is done using RSF's iGuide®, a very powerful yet user friendly PC-based programming tool.

### Simple to use

No Display! Users are unanimous: "it is even simpler to use - no questions asked!". Moreover, the **BASIC** integrates a vocal assistant that guides users in their handling.

### Lightweight and ergonomic

Its size, natural lines, and light weight (150g) make the **BASIC** particularly pleasant and comfortable to carry; even for long visits.

### Ideal for outdoor usage

Well suited for external usage: its' weather-proof electrical design and its 'tropicalisation' option make the **BASIC** uniquely suitable for external usage and for very humid environments.

### Ideal for boat, bus and city tours

The **BASIC** is extensively used for boat, bus and city tours because of its very large battery autonomy which makes it handling-free.

### Ideal for large sites and exhibitions

The ease of management and the very important operational costs savings made the **BASIC** the audioguide of choice for the largest sites and exhibition providers worldwide. These include the Prado museum in Spain, the Uffizi in Italy, and Premier exhibitions.



Commercial Division  
RSF Europe sa

10b, route d'Arlon  
L-7471 Saeul  
G.D. of Luxembourg

Tel. +352 49 74 20 40  
Fax +352 49 74 20 50  
[info@rsf-int.com](mailto:info@rsf-int.com)  
[www.rsf-int.com](http://www.rsf-int.com)



Manufacturer  
RSF

45, Av. Marcel Dassault  
(Parc de la Plaine)  
31500 Toulouse - France

Tel. +33 5 61 20 79 09  
Fax +33 5 61 80 00 94  
[www.rsf-europe.com](http://www.rsf-europe.com)

# PortaDAP BASIC



## Technical Specifications

### Audio parameters

Audio Format .....	High quality audio compression using SR3
Bandwidth .....	20Hz to 20KHz
Distortion .....	Below 0,01%
Dynamic .....	92 dB

### General parameters

Recording time capacity .....	Minimum of 24 hours and up (depending on memory)
languages/versions .....	32
Number of messages .....	900
Storage support .....	Flash card memory

### Programming

iGuide: user-friendly and powerful

**Content transfer**..... Memorec: fast transfers via USB port

**Theft protection**..... Integrated RFID alarm tag

### Buttons

Keypad .....	12 (0-9; Play/Pause; Stop; Volume +/-)
--------------	--

### Indicators

Playing .....	1 green led
---------------	-------------

Battery level .....	1 red led
---------------------	-----------

### Rechargeable batteries

Number .....	2
Type .....	AA alkaline batteries
Autonomy .....	350 hours of continuous playing =
.....	3 months (25 days) at 4 hours per day

**Enclosure**..... Moulded ABS plastic enclosure

**Dimensions**..... 258 x 58 x 25 mm

**Weight**..... 150 gr

### Environment

Temperature .....	-10°C to 50°C
-------------------	---------------

Relative Humidity .....	0-96%
-------------------------	-------

**Warranty**..... 2 years; can be extended up to 5 years



Visually impaired keypad version

## Optional accessories

Ref. MCD50-PB..... Distribution and transportation rack for 50 units

Ref. Catele..... One to five content transferring cable

Ref. iGuide..... PC-based software for encoding and programming the audio content (free of charge)

Ref. Memorec..... Hardware for transferring the content onto the audioguides, using PC's USB connection

Ref. AT Barrier..... Anti-theft protection barrier