•XYUNDAI IT CORP.

INDOOR DIGITAL SIGNAGE

PANORAMA VISION DISPLAY

CLASS 19" 38" 43"

MODEL C190MA C380ML C430ML

Broadcast your branding with Hyundai IT Digital Signage!

Panorama displays are characterized by their special aspect ratio whose height is less than half of its width. This brings the benefit that the panorama displays will fit into places where displays with a regular height can't be installed.

KEY FEATURES

- Special DOOH LCD Panel
- High Luminance & Contrast
- Metal Frame Housing
- Ultra-High Native Resolution
- Wide Viewing Angle
- High Connectivity
- Remote Control (RS232)





• YUNDAI IT CORP.

PANORAMA VISION DISPLAY

MODEL	CLASS
C190MA	19″
C380ML	38″
C430ML	43″

SPECIFICATIONS

Model		C190MA	C380ML	C430ML	
Panel	Screen Size	19"	38″	43"	
	Active Display Area	473.8 x 95.9	930.25 x 272.40	1059 x 264.96	
	Number of Pixels	1680 x 340	1366 x 400	1920 x 480	
	Aspect Ratio	4.9:1	3.4 : 1	4 : 1	
	Display Colors	16.7M	16.7M	16.7M	
	Brightness(typ)	300	450	700	
	Contrast Ratio	1000:1	1200:1	3000:1	
	Response Time (ms)	5	5	8	
	Viewing Angle (H°/V°)	170°/160°	178°/178°	178°/178°	
	Out Line Dimension	493.5 x 120.2 x 16.5	983.0 x 326.9 x 52.1	1084.0 x 289.0 x 58.0	
	Life Time	50,000Hrs	50,000Hrs	50,000Hrs	
Resolution	Monitor (Max)	1680 x 1050	1360 x 768	1920 x 1080	
	DTV (Max)	1080i	1080i	1080p	
Input	VGA (15pin D-Sub)	1	1	1	
	HDMI		1	1	
	DVI	1			
	Component (RCA)				
	PC Audio		1	1	
	Component Audio				
	RS232C	1	1	1	
Output		VGA, HDMI, RS232C, Speaker (10W x 2Ch)			
Auto Power Control (DPMS)		Yes			
Power	Input Voltage	100 - 240VAC	100 - 240VAC	100 - 240VAC	
	Consumption (typ) (W)	25W	115W	130W	
Feature	Tempered Glass	Option	Option	Option	
Auto Power Control		DPMS	DPMS	DPMS	
Dimension	Set (W x H x L)	496.5 x 123 x 60	986.0 x 330.7 x 101.7	1087 x 292 x 112.6	
	Packed (W x H x D)	TBD	1160 x 406 x 230	1160 x 406 x 230	
Weight : Without Glass	Set Weight (kg)	3kg	15kg	16kg	
		4kg	16.5kg	17.5kg	
Wall Mounting Hole (W x H mm)		75 x 75	600 x 200	600 x 200	
Operation	OSD Language	16 Lang	16 Lang	16 Lang	
	Temperature (°C)	0 - 40	0 - 40	0 - 40	
	Humidity (%)	20 - 80	20 - 80	20 - 80	
Approvals	EMI/EMC				
	Safety				
Accessories		Power Cord, HDMI Cable			
10000301165	Option	DVI-HDMI. D-SUB. RS-232C. Audio Cable			
	opuon	DAI-HDIMI' D-20R' H2-235C' Andio Papie			

FEATURES

Special Out-Of-Home LCD Panel

By using commercial grade LCD panels for Out-Of-Home applications, the HYUNDAI IT Digital Signage display can provide a higher brightness and contrast than standard LCD TV panels. Our LCD panel enables to operate for longer working time, deliver clear and bright image contents in the portrait or landscape format without any loss of quality.

Environmentally Responsible


Being compliant with the European RoHS directive and working with low power consumption during operation and power saving mode (<1W), the HYUNDAI IT Digital Signage is very energy efficient.

Multiple Video Input & Output

Providing an array of various professional input and output connectors [HDMI, DVI, RS232C, VGA], HYUNDAI IT Digital Signage can provide an easy, and flexible choice for connection to a full range of external A/V devices.

DIMENSIONS

C430ML [unit: mm]



Specifications and design are subject to change without notice. See www.hyundaiit.com for detailed information.

HYUNDAI IT EUROPE GmbH.

Kreuzberger Ring 7A, D-65205 Wiesbaden, Germany Tel: +49 (0) 611-20506-0 Fax: +49 (0) 611-20506-210 email : info@hyundaiit.eu